Baxter

DIAGNOSTIC CARDIOLOGY SUITE WITH SPIROMETRY



SPECIFICATION	DESCRIPTION	
Test Types Supported	FVC, SCV, MVV, Pre- and Post-bronchodilation	
Sensor Type	Pneumotach	
Accuracy & Reproducibility	Compliant with ATS/ERS 2005 Guidelines and ISO 26782 Guidelines	
Flow Range	+/- 14 L/sec	
Volume Range	0-14 L	
Resistance	Compliant with ATS/ERS 2005 Guideline and ISO 26782 Guidelines (Impedance does not exceed 0.15kPa/ [L/s] with flows up to 14 L/s]	
Interpretation	1991 ATS Interpretation Standards, Lung Age calculation available, Automatic Interpretation available, User-defined interpretation statements available	
Parameters	FVC, FIVC, FIV1, FIV1%, FEV0.5, FEV1, FEV2, FEV3, FEV5, FEV6, FEV0.5, FEV0.5%, FEV1%, FEV1/FVC, FEV2%, FEV3%, FEV5%, FEV6%, PEF, FEF25, FEF50, FEF75, FEF0.2-1.2, FEF25-75, FEF75-85, PIF, FIF50, FEF50/FIF50, FEV1/FEV6, FET, MEF25, MEF50, MEF75 SVC, ERV, IRV, VT, IC, BF, MV, Tin, Tex, Tin/Tex MVV, MV, VT, BF, DFRC	
Quality Checks	ATS Acceptability and ATS Reproducibility Effort-quality messages Audio and visual incentive for coaching patients	

MINIMUM SERVER REQUIREMENTS

SPECIFICATION	DESCRIPTION	
Processor	Performance equivalent to an Intel® Xeon® processor class, quad-core with hyperthreading	
Resolution	1024 x 768 or better	
RAM	Minimum 4 GB	
Operating System	Microsoft Server 2016 Microsoft Server 2019	
Hard Drive Capacity	Minimum 250 GB (If client: minimum 160 GB)	
System Disk	100 GB for OS and product installation (RAID recommended for data redundancy)	
Data Disks	550 GB hard drive space available HD controller with 128 MB read/write cache (RAID recommended for data redundancy)	

MINIMUM STANDALONE/CLIENT SPECIFICATIONS

SPECIFICATION	DESCRIPTION		
Operating Systems	Microsoft Windows 10 Professional and Enterprise (64-bit) Microsoft Windows 11 Professional and Enterprise Note: If installing ELI Link with Diagnostic Cardiology Suite system, requires 64-bit OS to operate both.		
Compatible Viewing Resolutions and Font Scaling	Resolutions: 1366×768, 1680×1050, 1920×1080, 1920×1200, 2736×1824	Font Scaling: 100%	
Processor	Performance equivalent or better than an Intel Core i3		
RAM	Minimum 4 GB		
Hard Drive Capacity	Minimum 250 GB (If client: minimum 160 GB)		
Archive	Network or external USB drive		
Software Installation	USB		
Network	100 Mbps connection or better		
USB Ports	Requires at least two USB 2.0 ports (spirometer external USB drive)		
Input Devices	Standard keyboard, mouse, spirometer		

MINIMUM CITRIX® XENAPP® REQUIREMENTS

SPECIFICATION	DESCRIPTION
Client Machines That Run Citrix® XenApp®	Microsoft Windows 10 Professional and Enterprise (64-bit) Microsoft Windows 11 Professional and Enterprise Citrix® Receiver Any internet browser supported by Citrix®
Citrix® Desktop Delivery Controller	Citrix® XenApp ® version 7.13 Any operating system supported by Citrix ®
Citrix® App Servers	Microsoft Server 2016 Microsoft Server 2019 Citrix® Virtual Delivery Agent 7.13

MINIMUM WINDOWS RDP REQUIREMENTS

SPECIFICATION	DESCRIPTION
Thin Clients Using Windows RDP	Microsoft Windows 10 Professional and Enterprise (64-bit) Microsoft Windows 11 Professional and Enterprise
Operating Systems for Servers Running Windows RDP	Microsoft Server 2016 Microsoft Server 2019

For more information, please contact your Baxter representative or call Baxter Customer Care on 1800 445 576.

ALWAYS READ THE LABEL AND FOLLOW THE DIRECTIONS FOR USE

CONTACT YOUR BAXTER REPRESENTATIVE FOR THE LATEST VERSIONS

Baxter reserves the right to make changes without notice in design, specifications and models.

Baxter, Diagnostic Cardiology Suite and ELI are trademarks of Baxter International Inc. or its subsidiaries.

Citrix and other marks appearing herein are trademarks of Citrix Systems, Inc., or its subsidiaries.

Intel and Xeon are trademarks of Intel Corporation or its subsidiaries.

Microsoft and Windows are trademarks of Microsoft Corporation.

AUTHORISED AUSTRALIAN SPONSOR Welch Allyn Australia Pty. Limited. 1 Baxter Drive, Old Toongabbie NSW 2146.

hillrom.com.au

